

# eco pelle / eco-leather / Kunstleder / simil cuir / ecopiel

## Cat A - Grimm Fr MP

### Application

Contract and domestic use

### Description

#### Composition

31% CO - 68% PVC- 1% PU

Weight g/m2 640

Width cm 140

### Tests

#### Abrasion

resistance cicli / cycles EN ISO 5470-2  
150000

#### Colour fastness to light (Xenotest)

UNI EN ISO 105-B02 7 colour change

#### Dry rubbing

ISO 105 X-12 4/5

#### Wet rubbing

ISO 105 X-12 4/5

#### Acid perspiration

ISO 105 E-04 4/5

#### Alcaline perspiration

ISO 105 E-04 4/5

#### Bending strenght cycles

UNI 4818-13 150000

#### Tensile strenght

ISO1421, Met.1 550 N warp, 300N weft

#### Tear strenght

ISO 4674-1 40 N warp, 45N weft

### Flame resistance

EN 1021-1 EN 1021-2

NF D 60-013

UNI 9175 CL. 1IM

BS 5852 crib 5


### Care

Clean with a damp cloth  
and mild soap.

Samples are purely indicative because of natural inconsistencies that occur in the raw materials. As a result there may be small differences in the product delivered.



1C8



4P2



4H8



5P4



101



2PB




2C7



5H3



5PE



2PA




2DJ




901



3CS




7P5




7FC




7EM



6VZ



6P1



6KH



6P7



8P8



8H4



8P9



5P3