

# pelle / soft -leather / Softleder / peau / piel

## Application

Contract and domestic use.

## Description

Thickness 0,9/1,0 mm

European raw hides

Chrome tannage

Through-dyeing Aniline

Finishing pigmented

Samples are purely indicative because of natural inconsistencies that occur in the raw materials. As a result there may be small differences in the product delivered.

## Tests

This item complies with the 3M test for oleo and hydro repellency. The Scotchgard treatment gives more protection and durability to leather.

Dry rub fastness  
UNI EN ISO 11640 > 3 Grey Scale

Light fastness  
UNI EN ISO 105-B02 > 3 Blue Scale

Tear resistance  
UNI EN ISO 3377-1 > 20 N

Flame resistance  
BS EN 1021-2:2006  
No Ignition  
BS EN 1021-1:2006  
No Ignition



EPD®

## Care

Dust with a soft and dry cloth for the normal cleaning. Stains can be treated with a wet cloth or cotton wool and with products for the cleaning initially more delicate like neutral soap or cleansing milk. Dry immediately after treatment. Never use abrasive or aggressive products like solvents, stain removers. Never steam it. Don't use shoe cleaning products. When a new product is used for cleaning, apply it in a "hidden" area to test its effectiveness and to avoid damages where more visible. Avoid placing leather near direct sun. Keep the leather away from heat sources. Dust regularly with a soft and dry cloth.




P3  
Fango chiaro




P10  
Grigio




P7  
Fango scuro



P4  
Bianco



P9  
Marrone scuro



P1  
Nero



P2  
Rosso